



Roll Feed Panel Ripper

High Production... Heavy Duty... American Parts

SPECIFICATIONS

- 15HP to 75HP 230V/460V/3PH Saw motor
- Standard arbor size is 3-15/16" diameter x 72" long with 1-15/16" precision bearings. Special arbor lengths available up to 108".
- 8 Steel feed rollers are driven top and bottom, giving positive, non-marking feed and long roller life (optional polyurethan rollers are available)
- Fixed feed speeds from 20-150fpm. 79fpm standard. Variable speed feed is available.
- Uses 10" diameter 4-3/16" bore blades.
- Rip 1/8" to 1-1/4" thick with 10" diameter blades. (Custom builds available with 12" and 14" diameter blades allow ripping of material up to 3-3/4" thick.
- Foot print: 40" x 96"
- Working height: 47-1/4"
- Dust ports: 4"(2x), 8"(1x)
- Blades mount to arbor using precision collars which allow setup changes of 10-15minutes.
- Optional: Arbor change out carts allow setup changes in 4 minutes

Simple Design, Low Cost, High Performance

Just like our other equipment

High Production...

One person can rip a bundle in 3-1/2 minutes

Off-The-Shelf Parts

So you can keep it running years from now



ANOTHER HIGH PRODUCTION WOODWORKING MACHINE BY LHI - BUILDERS OF SIMPLE, TOUGH MACHINES FOR 40 YEARS

Designed and Manufactured by Lauderdale-Hamilton, Inc.

732 Romie Hill Avenue • Box 165, Shannon, MS 38868 • Phone 662-767-3928 • Fax 662-767-3047 • sales@lauderdale-hamilton.com